

Uncontrolled document as of August 9, 2011. Refer to website for up to date specifications.

**LIGHTS**  
**2000**  
**SabreLite**



**Submersible** 

**SabreLite™ 2000 Flashlight**

This powerful flashlight was designed with one thing in mind: SAFETY. It carries more approvals than any other flashlight on the market today, making it safe for any hazardous environment or condition. The SabreLite is o-ring sealed with a twist-on shroud and comes with a polarity battery guard tray that safeguards against dangerous "outgassing" of hydrogen from an accidentally reversed cell. It is powered by 3 C alkaline cells, submersible, and has an ABS resin body which resists chemicals, corrosion, and extreme temperatures. Unlike ordinary flashlights that produce a yellow beam, the SabreLite's incredibly bright Xenon lamp produces a powerful collimated white beam. Pelican's SabreLite is the leader in quality and performance.

**Minimum Pack 6 ea.**

**Package Weight : 6.8 oz.**

**Assorted Packs available - 2 black, 2 yellow, 2 orange.**

**SabreLite™ 2000 Flashlight Specifications**

**SabreLite™ 2000 Flashlight Configurations**

Cat. #	Description
--------	-------------

High	
<b>LIGHT SOURCE</b>	Xenon
<b>BATTERIES</b>	3 C Alkaline (Not included)
<b>CHARGE TIME</b>	N/A
<b>VOLTAGE</b>	4.5
<b>LENGTH</b>	7.79" (19.8 cm)
<b>WEIGHT w/ BATTERIES</b>	12.8 oz. (0.36 kg)
<b>WEIGHT w/o BATTERIES</b>	5.31 oz. (0.15 kg)

2000 SabreLite™ 2000 Flashlight (Carded)






2000PL SabreLite™ 2000 Flashlight w/ Photoluminescent Shroud (Carded)

### NSN List

NSN #	Description
6230-01-281-3775	2000B Black
6230-01-295-1259	2000B Yellow
6230-01-324-2951	2000B Orange
6230-01-496-3640	2000 Zone 1 (Peli)
6240-01-493-6640	2004 Lamp Module

### SabreLite™ 2000 Flashlight Accessories

Cat. #	Description
2004	SabreLite™ 2000 Lamp Module
2003PL	Photoluminescent Shroud
8052OR	Traffic Wand (Orange)
8052YW	Traffic Wand (Yellow)

FL1 STANDARD		High	
<b>LIGHT OUTPUT</b>		53 LUMENS	
<b>RUNTIME (hours/min)</b>		5h	
<b>BEAM DISTANCE (meters)</b>		158m	
<b>PEAK BEAM INTENSITY (candela)</b>		6234cd	
<b>WATERPROOF &amp; SUBMERSIBLE</b>		1m	

### SabreLite™ 2000 Flashlight Approvals



Class I, Div. 2; Gp ABCD, T3C; Class II; Div. 2; Gp G.



Class I, II, Div. 2; Gp. ABCD/G, T3C.



Listed 4S67/E184884 Class I, Div. 1; Gp. C, D / Class I; Zone 1; Gp. IIA; IIB; T3C



10C-629-2



IEC Ex TSA06.0021X Ex ib e IIC T4 IP67

### Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
e-mail: [sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)