

XPP-5452G

Intrinsically Safe Dual-Function Headlamp

MARKET APPLICATIONS Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

DESCRIPTION This Intrinsically Safe dual-function headlamp features a multi-position tilt head design and includes a non-slip elastic

head strap for use on any hard hat. The top-mounted switch provides user-selectable high or low brightness spotlight

operation. Power comes from 3 AAA batteries (included).

CASE MATERIAL Engineered Polymer - Green

DIMENSIONS Length: 2.4 inches (61 mm) • Width: 1.9 inches (48 mm) • Depth: 1.8 inches (46 mm)

WEIGHT Weight: 3.5 oz. (99 g) with batteries installed

LENS Unbreakable polycarbonate with scratch resistant coating

LIGHT OUTPUT High-Brightness Spotlight: 180 lumens, Low-Brightness Spotlight: 90 lumens
ON/OFF Single Body Switch. High-Brightness Spotlight, Low-Brightness Spotlight
RUN-TIME High-Brightness Spotlight: 6 hours, Low-Brightness Spotlight: 19 hours

BATTERY 3 AAA batteries (included)

• CREE® LED technology – 50,000 + hours LED life

High-brightness spotlight, low-brightness spotlightFocused spotlight beam for distance illumination

· Engineered polymer housing

• Single switch located on top of light

Adjustable ratchet tilt head

Non-slip elastic head strap

· Heavy-duty rubber strap for hard hat applications

Dustproof / WaterproofImpact & chemical resistant3 AAA batteries (included)

WARRANTY Limited Lifetime Warranty


APPROVALS
















Intertek

ID 4001184 INTRINSICALLY SAFE SECURITE INTRINSEQUE

C € 0359

CLASS II & III GRPS E-G T135C CLASS I ZONE 0 AEx ia IIC T3 Ga CLASS I ZONE 0 Ex ia IIC T3 Ga © II 1 G Ex ia op is IIC T3 Ga Ex ia op is IIC T3 Ga Intertek ITS 13 ATEX27854X IECEX ITS 17.0002X -20°C ≤ Tamb ≤ +40°C 1.5V/Cell AAA Alkaline

SEE INSTRUCTION MANUAL VOIR MANUEL

MFG MM-YY